

S - HOOKS & LINKS



Zinc Plated 'S' - Hooks

Size	Overall Length	Hook Opening	Weight (lbs)	Vanguard Code
3 x 25 mm	1	1/8	0.066	2930 0030
4 x 37 mm	1 1/2"	5/32	0.132	2930 0040
5 x 45 mm	1 5/8	3/16	0.286	2930 0050
6 x 55 mm	2 1/8	1/4	0.485	2930 0060
8 x 76 mm	3 1/4	5/16	1.360	2930 0080
10 x 103 mm	4	3/8	1.710	2930 0100



Repair or Lap Links

- Mild Steel, Electro Galvanized

Size	WLL (lbs)	Pieces Per Carton	Weight (lbs)	Vanguard Code
3/16 x 1	240	100	0.03	2916 1210
1/4 x 2	400	100	0.04	2916 1620
5/16 x 2	950	50	0.17	2916 2020
3/8 x 2	1,250	50	0.26	2916 2420
1/2 x 2 1/2	1,525	50	0.53	2916 3225
5/8 x 2 1/2	1,000	50	0.81	2916 4025



Warning:

NEVER EXCEED WORKING LOAD LIMITS!
 ZINC PLATED S-HOOKS ARE NOT DESIGNED TO SUPPORT LOADS
 DO NOT USE S-HOOKS FOR LIFTING
 THESE LINKS MUST NOT BE USED FOR OVERHEAD LIFTING




LINKS

VGD Quick Links

- Mild Steel, Zinc Plated

Size	WLL (lbs)	Pieces Per Carton	Weight (lbs)	Vanguard Code
1/8	200	20	0.02	2918 0008
3/16	660	20	0.05	2918 0012
1/4	880	20	0.08	2918 0016
5/16	1,760	20	0.18	2918 0020
3/8	2,200	20	0.23	2918 0024
7/16	2,640	10	0.32	2918 0028
1/2	3,300	10	0.52	2918 0032



VGD Twin Clevis Links

- For use with Grade 70 or lower grade chains only
- Finish: Galvanized, altern. Black Body with Yellow Pins


Size	WLL (lbs)	Pieces Per Carton	Weight (lbs)	Vanguard Code
1/4 - 5/16	4,700	100	0.37	3936 5020
3/8	6,600	100	0.54	3936 5024
1/2	11,300	50	1.18	3936 5032



VGD Pear Shaped Snap Links

- Mild Steel, Zinc Plated

Size	WLL (lbs)	Pieces Per Carton	Weight (lbs)	Vanguard Code
1/8	200	20	0.02	2918 1008
3/16	220	20	0.06	2918 1012
1/4	260	20	0.08	2918 1016
5/16	500	20	0.14	2918 1020
3/8	770	20	0.28	2918 1024
1/2	1,400	10	0.72	2918 1032



Warning:

**NEVER EXCEED WORKING LOAD LIMITS!
THESE LINKS MUST NOT BE USED FOR OVERHEAD LIFTING**