



TURNBUCKLES


Forged Turnbuckles

- Meeting the requirements of U.S. Fed. Spec. FF-T-791B Type 1, Form 1 (open body)
- Hexagon heads forged into bodies permit fast and easy adjustments
- Forged Carbon Steel, hot dip galvanized, end-fitting quenched & tempered
- Design Factor 5:1
- Available in various configurations (see Prefix*)

Prefix*	
Eye & Eye	2920
Hook & Eye	2921
Jaw & Eye	2922
Hook & Hook	2923
Jaw & Jaw	2925



Size (Diameter x Take-Up)		Overall Dimension (closed)	WLL (lbs)		Weight (lbs)			Vanguard Suffix Code*
Diameter	Take-Up		H & H H & E	E & E J & J J & E	Eyes or Hooks	Jaw & Eye	Jaw & Jaw	
3/8	6	11 7/8	1,000	1,200	0.71	0.76	0.81 1024
1/2	6	13 5/16	1,500	2,200	1.45	1.53	1.61 1032
1/2	9	16 5/16	1,500	2,200	1.68	1.71	1.74 2032
1/2	12	19 5/16	1,500	2,200	2.00	2.06	2.11 3032
5/8	6	15 1/2	2,250	3,500	2.35	2.35	3.02 1040
5/8	9	18 1/2	2,250	3,500	2.88	3.06	2.88 2040
5/8	12	21 1/2	2,250	3,500	3.78	3.78	3.38 3040
3/4	6	17	3,000	5,200	3.64	3.87	4.11 1048
3/4	9	20	3,000	5,200	4.31	4.30	5.10 2048
3/4	12	23	3,000	5,200	5.08	5.36	5.65 3048
3/4	18	29	3,000	5,200	6.29	6.57	6.86 4048
7/8	12	24 5/8	4,000	7,200	7.35	7.76	8.17 3056
7/8	18	30 5/8	4,000	7,200	9.35	9.24	9.13 4056
1	12	26 5/8	5,000	10,000	11.23	11.20	11.18 3100
1	18	32 5/8	5,000	10,000	13.23	13.30	14.60 4100
1	24	38 5/8	5,000	10,000	16.58	16.30	17.30 5100
1 1/4	12	29 7/8	5,000	15,200	17.90	19.40	20.91 3116
1 1/4	18	35 7/8	5,000	15,200	22.85	24.18	25.50 4116
1 1/2	12	32 3/8	7,500	21,400	27.94	28.99	30.05 3132
1 1/2	18	38 3/8	7,500	21,400	33.19	32.38	31.56 4132
1 1/2	24	44 3/8	7,500	21,400	37.69	39.18	40.67 5132
2	24	51 3/4		37,000	89.90	94.60	100.00 5200



Warning:

NEVER EXCEED WORKING LOAD LIMITS!
 TURNBUCKLES ARE DESIGNED FOR STRAIGHT (IN-LINE) PULLS ONLY!
 DO NOT RE-USE TURNBUCKLES SHOWING SIGNS OF DEFORMATION OR DAMAGED THREADS!